

The diagram illustrates the architecture of a secure mail system. It includes the following components and their interactions:

- USPS Certificate Authority (10)**: The central authority for certificates and public keys.
- Operations Center (12)**: Receives the Certificate/Public Key & Certificate ID from the USPS Certificate Authority (10).
- PGD (14)**: Receives data from the Operations Center (12) and outputs to the printer (18). It is associated with the Public Key, Private Key, & Certificate ID.
- Printer (18)**: Outputs the Digital Signature & Certificate ID (22) to the USPS Distribution Center (Verifier) (20a).
- USPS Distribution Center (Verifier) (20a)**: Receives the Digital Signature & Certificate ID (22) and outputs the Valid (20b) status to the USPS Distribution Center (Destination) (20b).
- USPS Distribution Center (Destination) (20b)**: The final destination for the mail.
- USPS Certificate Authority (10)**: Also receives the Certificate/Public Key from the USPS Distribution Center (Verifier) (20a).

The flow of data is as follows:

- The USPS Certificate Authority (10) sends the Certificate/Public Key & Certificate ID to the Operations Center (12).
- The Operations Center (12) sends data to the PGD (14).
- The PGD (14) outputs to the printer (18).
- The printer (18) outputs the Digital Signature & Certificate ID (22) to the USPS Distribution Center (Verifier) (20a).
- The USPS Distribution Center (Verifier) (20a) outputs the Valid (20b) status to the USPS Distribution Center (Destination) (20b).
- The USPS Distribution Center (Verifier) (20a) also sends the Certificate/Public Key back to the USPS Certificate Authority (10).

FIG. 1

096035 000000




FIG. 2






FIG. 3



## Generation and Distribution of Keys

FIG. 4

0360347-015-0000



## Dispensing & Evidencing Postage Indicia

FIG. 5

```
graph TD; 90[Receive the verification keys V_i^Dest and key ID's I_i^Dest generated as a function of the destination region serviced by the distribution center] --> 92[In response to receiving a mail piece, determine the mail piece's destination region]; 92 --> 94[If the distribution center is not within the destination region, transfer the mail piece to the distribution center within the destination region]; 94 --> 96[If the distribution center is within the destination region, begin verifying the postage indicia by reading the digital signature and the key ID from the indicia]; 96 --> 98[Use the key ID read from the indicia to retrieve the corresponding verification key from the table of all verification keys]; 98 --> 100[Use the retrieved verification key to compute a digital signature for the indicia, and compare the computed digital signature with the digital signature from the postage indicia to verify the indicia];
```

900

90 Receive the verification keys  $V_i^{\text{Dest}}$  and key ID's  $I_i^{\text{Dest}}$  generated as a function of the destination region serviced by the distribution center

92 In response to receiving a mail piece, determine the mail piece's destination region

94 If the distribution center is not within the destination region, transfer the mail piece to the distribution center within the destination region

96 If the distribution center is within the destination region, begin verifying the postage indicia by reading the digital signature and the key ID from the indicia

98 Use the key ID read from the indicia to retrieve the corresponding verification key from the table of all verification keys

100 Use the retrieved verification key to compute a digital signature for the indicia, and compare the computed digital signature with the digital signature from the postage indicia to verify the indicia

## FIG. 6